



CHANGZHOU FENFEI TECHNOLOGY CO.,LTD

Display Refrigeration

Merchandisers	P1-11
- Refrigerators	P1-7
- Freezers	P8-11
Back Bar Coolers	P12
- Back Bar Refrigerators	P12



NE-08C	
Volume:	8L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	72W
Refrigerant:	R600a
Unit Size:	220*514*430mm
Carton Size:	301*561*430mm
N.W/G.W:	14KG/15.5KG
Temperature:	2 ~ 10°C
Loading Quantity(20/40/40HQ)	380/780/936

NE-21C	
Volume:	21L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	330*405*480mm
Carton Size:	421*481*542mm
N.W/G.W:	15KG/16.5KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	264/528/528

NE-25CL	
Volume:	25L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	72W
Refrigerant:	R600a
Unit Size:	330*350*615mm
Carton Size:	386*381*664mm
N.W/G.W:	16KG/17.5KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	270/540/720



NE-26C	
Volume:	26L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	83W
Refrigerant:	R600a
Unit Size:	600*495*297mm
Carton Size:	671*556*354mm
N.W/G.W:	17KG/19KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	192/408/476

NE-35C	
Volume:	35L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	365*460*510mm
Carton Size:	447*527*542mm
N.W/G.W:	16KG/18KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	228/456/456

NE-42CL	
Volume:	42L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	400*415*733mm
Carton Size:	484*464*782mm
N.W/G.W:	20KG/22KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	180/360/360



NE-52C	NE-52CR
Volume:	52L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	435*495*510mm
Carton Size:	517*562*542mm
N.W/G.W:	19KG/21KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	176/368/368

NE-55CL	
Volume:	55L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	420*455*793mm
Carton Size:	502*529*842mm
N.W/G.W:	23KG/25KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	88/184/276

NE-66C	
Volume:	66L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	360*385*1067mm
Carton Size:	421*456*1104mm
N.W/G.W:	27KG/29KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	130/280/330



NE-70C	NE-70CR
Volume:	70L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	435*500*695mm
Carton Size:	517*562*727mm
N.W/G.W:	24KG/26KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	132/276/276

NE-75CL	
Volume:	75L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	103W
Refrigerant:	R600a
Unit Size:	360*410*1350mm
Carton Size:	421*461*1400mm
N.W/G.W:	29KG/32KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	115/220/220

NE-80CL	
Volume:	80L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	103W
Refrigerant:	R600a
Unit Size:	460*470*933mm
Carton Size:	542*539*982mm
N.W/G.W:	29KG/32KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	80/176/176



NE-98C	
Volume:	98L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	103W
Refrigerant:	R600a
Unit Size:	480*485*852mm
Carton Size:	562*552*887mm
N.W/G.W:	31KG/34KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	80/168/252



NE-105CL		NE-105CLB	
Volume:	105L	Volume:	105L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz	Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	130W	Input Power:	130W
Refrigerant:	R600a	Refrigerant:	R600a
Unit Size:	360*385*1890mm	Unit Size:	360*385*1890mm
Carton Size:	421*446*1939mm	Carton Size:	421*446*1939mm
N.W/G.W:	38KG/42KG	N.W/G.W:	38KG/42KG
Temperature:	0 ~ 10°C	Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	65/140/168	Loading Quantity(20/40/40HQ)	65/140/168



NE-110C	
Volume:	110L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	103W
Refrigerant:	R600a
Unit Size:	480*510*860mm
Carton Size:	557*562*974mm
N.W/G.W:	31KG/34KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	80/168/252



NE-150CL	
Volume:	150L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	150W
Refrigerant:	R600a
Unit Size:	420*430*1880mm
Carton Size:	466*511*1939mm
N.W/G.W:	48KG/53KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	55/115/115



NE-175C	
Volume:	175L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	150W
Refrigerant:	R600a
Unit Size:	420*450*1817mm
Carton Size:	466*511*1869mm
N.W/G.W:	50KG/54KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	55/110/140



NE-235CL	
Volume:	235L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	190W
Refrigerant:	R600a
Unit Size:	535*555*1845mm
Carton Size:	581*606*1904mm
N.W/G.W:	65KG/70KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	36/76/100



NE-260C	
Volume:	260L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	180W
Refrigerant:	R600a
Unit Size:	450*575*1975mm
Carton Size:	511*646*2029mm
N.W/G.W:	80KG/83KG
Temperature:	0 ~ 10°C
Loading Quantity(20/40/40HQ)	40/82/102



NE-430CL	
Copacity:	430L
Inner Temperature:	1 ~ 10°C
Door:	1
Power:	430W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	620x630x2000mm
Net Weight:	80kg



NE-860CL	
Copacity:	860L
Inner Temperature:	1 ~ 10°C
Divider:	2
Power:	560W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1100x630x2000mm
Net Weight:	110kg



NE-1200CL	
Copacity:	1200L
Inner Temperature:	1 ~ 10°C
Divider:	3
Power::	810W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1680x630x2000mm
Net Weight:	160kg



NE-380B

Copacity:	380L
Inner Temperature:	1 ~ 10°C
Door:	1
Power:	330W
Cooling method:	Circulating air cooling+automated frost
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	550x630x1980mm
Net Weight:	60kg

NE-780B

Copacity:	780L
Inner Temperature:	1 ~ 10°C
Divider:	2
Power:	460W
Cooling method:	Circulating air cooling+automated frost
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1100x630x1980mm
Net Weight:	110kg

NE-1100B

Copacity:	1100L
Inner Temperature:	1 ~ 10°C
Divider:	3
Power::	660W
Cooling method:	Circulating air cooling+automated frost
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1680x630x1980mm
Net Weight:	160kg



	NE-420CK	NE-560CK	NE-700CK	NE-840CK
Copacity:	420L	560L	700L	840L
Inner Temperature:	2 ~ 8°C	2 ~ 8°C	2 ~ 8°C	2 ~ 8°C
Cooling Method:	Air-cooling	Air-cooling	Air-cooling	Air-cooling
Power:	500W	550W	650W	750W
Voltage:	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz
Product Size:	900*660*1200mm	1200*660*1200mm	1500*660*1200mm	1800*660*1200mm
Packing Size:	970*730*1270mm	1270*730*1270mm	1570*730*1270mm	1870*730*1270mm
Net weight/Gross weight:	120kg/135kg	145kg/160kg	170kg/185kg	200kg/215kg



	NE-420CH	NE-560CH	NE-700CH	NE-840CH
Copacity:	420L	560L	700L	840L
Inner Temperature:	2 ~ 8°C	2 ~ 8°C	2 ~ 8°C	2 ~ 8°C
Cooling Method:	Air-cooling	Air-cooling	Air-cooling	Air-cooling
Power:	500W	550W	650W	750W
Voltage:	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz	110V ~ 240V/50Hz ~ 60Hz
Product Size:	900*660*1200mm	1200*660*1200mm	1500*660*1200mm	1800*660*1200mm
Packing Size:	970*730*1270mm	1270*730*1270mm	1570*730*1270mm	1870*730*1270mm
Net weight/Gross weight:	120kg/135kg	145kg/160kg	170kg/185kg	200kg/215kg



NE-330CK	
Copacity:	330L
Inner Temperature:	1 ~ 8°C
Door:	1
Power:	330W
Cooling method:	Circulating air cooling + no defrosting required
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	620*600*1985mm
Net Weight:	60kg

NE-660CK	
Copacity:	660L
Inner Temperature:	1 ~ 8°C
Divider:	2
Power:	520W
Cooling method:	Circulating air cooling + no defrosting required
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1100x600x1985mm
Net Weight:	110kg

NE-990CK	
Copacity:	990L
Inner Temperature:	1 ~ 8°C
Divider:	3
Power::	660W
Cooling method:	Circulating air cooling + no defrosting required
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1680x600x1985mm
Net Weight:	160kg



NE-04D	
Volume:	4L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	264*369*310mm
Carton Size:	325*455*385mm
N.W/G.W:	10.5KG/12KG
Temperature:	-22 ~ 0°C
Loading Quantity(20/40/40HQ)	455/945/1134

NE-05D	
Volume:	5L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	85W
Refrigerant:	R600a
Unit Size:	264*455*310mm
Carton Size:	346*562*385mm
N.W/G.W:	11KG/13KG
Temperature:	-22 ~ 0°C
Loading Quantity(20/40/40HQ)	392/830/972

NE-16D	
Volume:	16L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	76W
Refrigerant:	R600a
Unit Size:	230*517*510mm
Carton Size:	301*581*569mm
N.W/G.W:	15KG/17KG
Temperature:	-10 ~ 0°C
Loading Quantity(20/40/40HQ)	304/624/624



NE-18D	
Volume:	18L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	83W
Refrigerant:	R600a
Unit Size:	490*495*297mm
Carton Size:	561*556*354mm
N.W/G.W:	12KG/14KG
Temperature:	-10 ~ 0°C
Loading Quantity(20/40/40HQ)	240/504/588

NE-21D	
Volume:	21L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	115W
Refrigerant:	R290
Unit Size:	400*430*545mm
Carton Size:	477*511*586mm
N.W/G.W:	22KG/24KG
Temperature:	-18 ~ -25°C
Loading Quantity(20/40/40HQ)	192*400/400

NE-25DL	
Volume:	25L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	128W
Refrigerant:	R290
Unit Size:	400*390*733mm
Carton Size:	484*464*782mm
N.W/G.W:	23KG/25KG
Temperature:	-18 ~ -25°C
Loading Quantity(20/40/40HQ)	180/360/360



NE-50DL	
Volume:	50L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	155W
Refrigerant:	R290
Unit Size:	460*445*817mm
Carton Size:	542*539*866mm
N.W/G.W:	30KG/33KG
Temperature:	-18 ~ -25°C
Loading Quantity(20/40/40HQ)	80/176/264



NE-55D	
Volume:	55L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	155W
Refrigerant:	R290
Unit Size:	595*555*623mm
Carton Size:	666*601*664mm
N.W/G.W:	34KG/37KG
Temperature:	-18 ~ -25°C
Loading Quantity(20/40/40HQ)	81/171/228



NE-98D	
Volume:	98L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	210W
Refrigerant:	R290
Unit Size:	595*555*842mm
Carton Size:	666*601*878mm
N.W/G.W:	51KG/55KG
Temperature:	-18 ~ -25°C
Loading Quantity(20/40/40HQ)	54/114/171



NE-105DL	
Volume:	105L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	190W
Refrigerant:	R290
Unit Size:	360*385*1890mm
Carton Size:	456*461*1959mm
N.W/G.W:	42KG/45KG
Temperature:	-18 ~ -22°C
Loading Quantity(20/40/40HQ)	65/140/140



NE-480DL

Copacity:	480L
Inner Temperature:	-18 ~ -22°C
Door:	1
Power:	800W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	620x700x2150mm
Net Weight:	120kg

NE-1050DL

Copacity:	1050L
Inner Temperature:	-18 ~ -22°C
Divider:	2
Power:	1600W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1260x700x2150mm
Net Weight:	170kg

NE-1550DL

Copacity:	1550L
Inner Temperature:	-18 ~ -22°C
Divider:	3
Power::	2100W
Refrigerant:	R290
Voltage:	110V ~ 240V/50Hz ~ 60Hz
Unit Dimensions:	1860x700x2150mm
Net Weight:	220kg



NE-130DT	
Volume:	130L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	210W
Refrigerant:	R290
Temperature:	-25 ~ 5°C
Cooling Method:	Direct Cooling
Unit Size:	580*690*820mm
Carton Size:	620*740*870mm
N.W/G.W:	30KG/33KG

NE-260DT	
Volume:	260L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	270W
Refrigerant:	R290
Temperature:	-25 ~ 5°C
Cooling Method:	Direct Cooling
Unit Size:	1094*598*820mm
Carton Size:	1130*650*880mm
N.W/G.W:	49KG/52KG

NE-360DT	
Volume:	360L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	330W
Refrigerant:	R290
Temperature:	-25 ~ 5°C
Cooling Method:	Direct Cooling
Unit Size:	1294*598*820mm
Carton Size:	1330*650*880mm
N.W/G.W:	51KG/55KG



NE-380DT	
Volume:	380L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	330W
Refrigerant:	R290
Temperature:	-25 ~ 5°C
Cooling Method:	Direct Cooling
Unit Size:	1225*650*820mm
Carton Size:	1260*700*880mm
N.W/G.W:	51KG/55KG

NE-450DT	
Volume:	450L
Voltage /Frequency	110V ~ 240V /50Hz ~ 60Hz
Input Power:	380W
Refrigerant:	R290
Temperature:	-25 ~ 5°C
Cooling Method:	Direct Cooling
Unit Size:	1500*650*820mm
Carton Size:	1530*700*950mm
N.W/G.W:	65KG/70KG



NE-100C	NE-100CS
Capacity:	100L
Inner Temperature:	2 ~ 10°C
Door:	1
Cooling Type:	Air Cooling
Power:	160W
Refrigerant:	R600a
Voltage:	110V ~ 240V/50Hz ~ 60Hz
External dimensions:	500*535*830mm
Net Weight:	39kg

NE-200C	NE-200CS
Capacity:	200L
Inner Temperature:	2 ~ 10°C
Door:	2
Cooling Type:	Air Cooling
Power:	190W
Refrigerant:	R600a
Voltage:	110V ~ 240V/50Hz ~ 60Hz
External dimensions:	900/535/830mm
Net Weight:	56kg



NE-300C	NE-300CS
Capacity:	300L
Inner Temperature:	2 ~ 10°C
Door:	3
Cooling Type:	Air Cooling
Power:	220W
Refrigerant:	R600a
Voltage:	110V ~ 240V/50Hz ~ 60Hz
External dimensions:	1350*535*830mm
Net Weight:	76kg

NE-400C	NE-400CS
Capacity:	400L
Inner Temperature:	2 ~ 10°C
Door:	4
Cooling Type:	Air Cooling
Power:	380W
Refrigerant:	R600a
Voltage:	110V ~ 240V/50Hz ~ 60Hz
External dimensions:	1800*535*830mm
Net Weight:	112kg



WECHAT



WHATSAPP

CHANGZHOU FENFEI TECHNOLOGY CO,LTD

**BANSHANG STREET,LIJIA,WUJIN DISTRICT,CHANGZHOU CITY,
JIANGSU PROVINCE,CHINA,213165**

TEL:+86 519 86731588

E-mail:leo@nuelead.com

www.nuelead.com